


Product data sheet

TRUSYS FLEX WALLWASHER 50W 865 WW CL WT DALI
4099854191411
LEDVANCE



Luminaire inserts with asymmetric wallwasher light distribution, up to 175 lm/W. Product features: Beam angle wall washer: 1x40°. Click into place solution with smart click buttons. Luminous efficacy: up to 175 lm/W. Fixed luminare taps. Luminaire versions available with on-off or IoT-ready DALI-2 driver. Steel-sheet housing. Lens material: PMMA. Type of protection: IP40. Product benefits: Wall washer light distribution for directed wall illumination. Easy installation, no tools required for connection. Energy saving and cost-effective. Flexible application due to a range of different lumen packages and beam angles. 5 years guarantee. Areas of application: Direct replacement for luminaires with fluorescent lamps. Industry halls, high rack warehouse, hardware stores. Discounters, supermarkets. Equipment / Accessories: Mounting rail with fixed integrated 5- and 8-pole cable.

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	50 W	CRI	80
Total flux	8600 lm	LOR	100%
Luminous efficacy	172 lm/W	Total power	50 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.06 in
Width: 3.06 in
Height: 1.55 in
Weight: 1.75 kg

Adjustability

Fixed

Design

Material impression: Stainless steel
Color of housing: White

Electric

System power: 50 W
Appliance Class: I

Protection

IP: 40
IK: 04
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...104°F