# Product data sheet

MINI MULTIPLE TRIMLESS FOR LED 4000K FLOOD GE WHITE STRUC 13131009+14070809

MODULAR






1 v I ED




Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your chouce. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with LED by adding the M-LED70 to your recessed spot.

#### Light output 1



I X LED	
Nominal lamp power	6.2 W
Lamp flux	590 lm
Luminous efficacy	95 lm/W
CCT	4000 K
CRI	90

LOR	100%
Total flux	590 lm
Total power	6.2 W



1 x LED	
Nominal lamp power	9.2 W
Lamp flux	792 lm
Luminous efficacy	86 lm/W
CCT	4000 H
CRI	90

LOR	100%
Total flux	792 lm
Total power	9.2 W

#### Mounting mode

Ceiling recessed, Wall recessed

## Shape and measurements

Length: 4.72 in Width: 4.72 in Height: 4.37 in Weight: 0.67 kg

## Adjustability

Cardanic

#### Electric

System power: 6.2-9.2 W Appliance Class: III

### Protection

IP: 20