# Product data sheet

HIGH5 TYPE II GREY 23W 3000K RA>70
8246087915
SG ARMATUREN



IP 66 IK 08

Design: Christian Hvidt Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II. Light distribution Type II Light technic LED 23W 3000K Ra>70 SDCM 4 L80/B10 >100,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class II IP66 IK08 Energy and approvals A++ CE Materials and finish Housing: Die-cast aluminium Colour: Grey (structure 2150 sablé) Optics: Glass Mounting/Connection Post - top (Ø60mm), Outdoor Cable 2x1mm² 6m Wind projected area: 385cm² - Max 4.2 kg Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 23 W | CRI | 70 |
| Total flux | 2780 lm | LOR | 100% |
| Luminous efficacy | 121 lm/W | Total power | 23 W |

### Mounting mode

Pole top mounted

### Shape and measurements

Length: 17.52 in
Width: 6.67 in
Height: 7.68 in

### Adjustability

Fixed

### Electric

System power: 23 W
Appliance Class: II

### Protection

IP: 66
IK: 08