

Product data sheet

LED PFM HIGHBAY SC 200W 865 277V
4058075464452
LEDVANCE




IP
65

IK
08

LEDVANCE® LED PERFORMANCE SENSOR COMPATIBLE HIGH BAY is a reliable and high efficiency LED High bay with aluminum die-cast housing for both industry and commercial applications. It provides a performance LED alternative to traditional High bays. The range is available in 2 housing sizes for 4 different wattages to meet most of the application requirements. The motion sensor offers an additional energy saving, It's an ideal solution for either retrofit or new construction. High system efficiency up to 140lm/W. 1-10V dimming. Be compatible with LEDVANEC HIGHBAY MOTION SENSOR. SMD LED design to maximize product reliability. Standard CCT: 4000K, 6500K, CRI >80. Aluminum die-cast housing, UV resistant high efficacy PC lens. IP65. Water and dust proof IK08 vandal-protected. Available in black housing. Long 50,000hr lifetime reduces maintenance costs. Pre-wired with 500mm flying cable (AU version with 1500mm flex and plug). Safety compliance certificates: CB.

Light output 1 (integrated)



Lamp type	LED	CCT	6800 K
Nominal lamp power	200 W	CRI	80
Total flux	28000 lm	LOR	100%
Luminous efficacy	140 lm/W	Total power	200 W

Mounting mode

Pendant

Shape and measurements

Height: 0.39 in
Diameter: 11.06 in

Adjustability

Height adjustable

Electric

System power: 200 W

Protection

IP: 65
IK: 08