Product data sheet


SLOIN TW A CL LED1600-830-60 L543 PC/PCO
42184168
ZUMTOBEL



IP 20 IK 07


Corner luminaire for LED light line with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 1800 lm, Luminaire efficacy: 58 lm/W. Colour rendering Ra > 80, colour temperature 3000 K to 6000K. Luminaire of aluminium, silver powder coated. Luminaire uniformly bright over 100% of the surface. Luminaire consists of housing, gear tray and wiring. Luminaire wired with halogen-free leads. Degree of protection: IP20. Dimensions: 543 x 76 x 98 mm weight: 5 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15.5 W	CRI	80
Total flux	900 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	15.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15.5 W	CRI	80
Total flux	900 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	15.5 W

Mounting mode

Pendant

Shape and measurements

Length: 21.38 in
Width: 2.99 in
Height: 3.86 in
Weight: 5 kg

Electric

System power: 31 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE, ENEC

Design

Material impression: Aluminum

Color of housing: Silver gray