Product data sheet


IMAX II SQUARE ADJUSTABLE MP 92726
24218 9220
DELTA LIGHT



IP 20


Luminaire, ceiling recessed (indoor use) from Deltalight, named iMAX II SQUARE ADJUSTABLE MP 92726, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 98 mm is needed and a min. depth for recessing of 155 mm. This luminaire is equipped with LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: lens 26°.

Light output 1




1 x LED

Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	17 W	LOR	73%
Lamp flux	2009 lm	Total flux	1462 lm
Luminous efficacy	118 lm/W	Total power	17 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	15 W	LOR	73%
Lamp flux	1830 lm	Total flux	1331 lm
Luminous efficacy	122 lm/W	Total power	15 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	17 W	LOR	73%
Lamp flux	2009 lm	Total flux	1462 lm
Luminous efficacy	118 lm/W	Total power	17 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	15 W	LOR	73%
Lamp flux	1830 lm	Total flux	1331 lm
Luminous efficacy	122 lm/W	Total power	15 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	17 W	LOR	73%
Lamp flux	2009 lm	Total flux	1462 lm
Luminous efficacy	118 lm/W	Total power	17 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	17 W	LOR	73%
Lamp flux	2009 lm	Total flux	1462 lm
Luminous efficacy	118 lm/W	Total power	17 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	15 W	LOR	73%
Lamp flux	1830 lm	Total flux	1331 lm
Luminous efficacy	122 lm/W	Total power	15 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	15 W	LOR	73%
Lamp flux	1830 lm	Total flux	1331 lm
Luminous efficacy	122 lm/W	Total power	15 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	15 W	LOR	73%
Lamp flux	1830 lm	Total flux	1331 lm
Luminous efficacy	122 lm/W	Total power	15 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	17 W	LOR	73%
Lamp flux	2009 lm	Total flux	1462 lm
Luminous efficacy	118 lm/W	Total power	17 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.33 in
Width: 4.33 in
Height: 0.08 in
Weight: 0.5 kg

Electric

System power: 12-17 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE