Product data sheet


KASKAD FIXED MEDIUM BLACK LL 927
73370
FAGERHULT



IP 44

Installation Recessed mounting in unventilated or ventilated suspended ceilings. Assembly springs for quick assembly included. Separate ballast box for flexible installation. An assembly plate must be used when mounting on soft tile ceilings Do not cover with insulation. For detailed information, please refer to the installation instructions. Connection Connections are made to the independent LED driver. The luminaire is delivered with interconnecting cable. Design Luminaire body and visible edge ring of sheet steel in white (RAL 9016) structured enamel. Heatsink in black enamelled aluminium. Louvre Specular reflector in anodised aluminium. Diffusing frosted glass raised in the reflector above structured enamelled black baffle. Miscellaneous IP 44 under suspended ceiling, IP 20 above suspended ceilings. Luminaire body class III. The supplied driver class II must be connected to a functional earth. For loads in the suspended ceiling system, follow the selected suspended ceiling supplier's recommendation.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	11 W	CRI	90
Total flux	869 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	11 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.33 in
Width: 12.20 in
Height: 3.78 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 11 W
Appliance Class: II

Protection

IP: 44