

Product data sheet

RBXL 123 L40
RUBIX LINEAR
DEXTRA




IP
20



Rubix Linear - 1200mm x 300mm, Recessed linear luminaire, white powder coated steel body, individual cells with opal surround trim for precise optical control. Options: E3 - Emergency control gear (661 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence BL - Black finish WH - White finish BLK - Black Cell Surround BLE - Blue Cell Surround ORA - Orange Cell Surround RED - Red Cell Surround

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24.6 W	CRI	80
Total flux	3236 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	4%
		Total power	24.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 49.61 in

Width: 9.06 in

Height: 2.56 in

Adjustability

Fixed

Electric

System power: 24.6 W

Ballast: ECG

Protection

IP: 20

Designation labels: CE