Product data sheet


161 LED DAMP-PROOF LIGHT FITTING
161 15L60 IFS 865 DV P5X2,5 (16119 1000)
SCHUCH



IP 65 IK 09

LED damp-proof light fitting, 39 W, 6160 lm, 158 lm/W, Class I, IP65, symmetrical wide beam, 6500 K, CRI≥ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PC satined, Closure Stainless steel (1.4571), Housing Glass fibre reinforced polyester, Colour grey, Through wiring (DV) 5x2.5 mm² PVC, for food areas. Sturdy LED damp-proof light fitting for application in food areas according to International Featured Standard Food. Highly impact-resistant glass fibre reinforced polyester housing and frosted PC diffuser with high impact resistance. Captive stainless steel clips, multi-part, incl. two safety clips, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 116,00 mm, Height 125,00 mm, Net weight 3,31 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	39 W	CRI	80
Total flux	6159 lm	LOR	100%
Luminous efficacy	158 lm/W	ULOR	7%
		Total power	39 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 61.89 in
Width: 4.57 in
Height: 4.92 in

Adjustability

Fixed

Electric

System power: 39 W
Appliance Class: I

Protection

IP: 65
IK: 09
Designation labels: CE