# Product data sheet


161 LED DAMP-PROOF LIGHT FITTING
161 15L60 IFS 865 DV P5X2,5 (16119 1000)
SCHUCH



IP 65 IK 09

LED damp-proof light fitting, 39 W, 6160 lm, 158 lm/W, Class I, IP65, symmetrical wide beam, 6500 K, CRI≥ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PC satined, Closure Stainless steel (1.4571), Housing Glass fibre reinforced polyester, Colour grey, Through wiring (DV) 5x2.5 mm² PVC, for food areas. Sturdy LED damp-proof light fitting for application in food areas according to International Featured Standard Food. Highly impact-resistant glass fibre reinforced polyester housing and frosted PC diffuser with high impact resistance. Captive stainless steel clips, multi-part, incl. two safety clips, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 116,00 mm, Height 125,00 mm, Net weight 3,31 kg.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 6500 K |
| Nominal lamp power | 39 W | CRI | 80 |
| Total flux | 6159 lm | LOR | 100% |
| Luminous efficacy | 158 lm/W | ULOR | 7% |
| | | Total power | 39 W |

### Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

### Shape and measurements

Length: 61.89 in
Width: 4.57 in
Height: 4.92 in

### Adjustability

Fixed

### Electric

System power: 39 W
Appliance Class: I

### Protection

IP: 65
IK: 09
Designation labels: CE