



Product data sheet

LINEAR COMPACT BATTEN 1200 20 W 3000 K
4058075099739
LEDVANCE



Compact luminaires with a wiring on the back side. Product features: Replacement for traditional T8 luminaires. Wiring at back side of luminaire. Translucent end caps. Connectible at the beginning of a light line with Linear Compact High Output luminaire. Versions with luminous flux 1000...2500 lm available. 3 different lengths available. High luminous efficacy: up to 100 lm/W. Glow Wire Test according to IEC 60695-2-12: 850 °C. Product benefits: Compact dimensions. Little space required thanks to compact dimensions. Seamless connection without visible cables when connected to Linear Compact High Output. High lumen output up to 2500 lm. Flexible application due to a wide range of available lengths of 600 to 1500 mm. Low flicker light thanks to special electronic control gear. 5 years guarantee. Areas of application: Direct replacement for luminaires with fluorescent lamps. Indoor applications. Corridors, entrance areas, stairwells, living rooms, basements. Accent lighting. Public areas. Cove lighting. Shelves, furniture integration or under cabinet mounting. Seamless linear lighting. Equipment / Accessories: Mounting clips included. Safety advice: All electrical connections must be made by a qualified person.. Caution, risk of electric shock..

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.26 in
Width: 1.06 in
Height: 1.50 in
Weight: 0.24 kg

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: White

Electric

System power: 20 W
Appliance Class: II

Protection

IP: 20
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F