


# Product data sheet

IMPACTF2 2X36W T26 HFD E3T L000  
96234368  
THORN LIGHTING




A high performance IP65 dust and moisture resistant luminaire with a high impact resistance. For 2 x 36W T26 lamp(s) with electronic - digital dimmable Slave luminaire for DSI control (other than DALI) circuit and integral 3 hour SelfTest emergency lighting function. Class I electrical. Canopy in light grey glass fibre reinforced polyester. Diffuser in polycarbonate with internal prisms. For surface or suspended mounting. Quick-fix installation brackets are supplied for surface mounting, optional accessory kits are available to help with other mounting options. Lamps to be ordered separately. Dimensions: 1294 x 167 x 125 mm Total power: 70.4 W Weight: 4.24 kg

## Light output 1 (emergency)



1 x General service incandescent lamp			
Nominal lamp power	36 W	LOR	72%
Lamp flux	238 lm	ULOR	12%
Luminous efficacy	26 lm/W	Total flux	171 lm
CCT	3000 K	Total power	6.5 W
CRI	80		

## Light output 2



2 x General service incandescent lamp			
Nominal lamp power	36 W	LOR	72%
Lamp flux	6700 lm	ULOR	12%
Luminous efficacy	137 lm/W	Total flux	9621 lm
CCT	3000 K	Total power	70.4 W
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 50.94 in  
Width: 6.57 in  
Height: 4.92 in  
Weight: 4.2 kg

## Electric

System power: 76.9 W  
Voltage: 230-240 V AC  
Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Design

Material impression: Plastic

## Protection

IP: 65

IK: 08

Designation labels: CE