


# Product data sheet

NADJA IV (1-ARMED)  
9.879.5507.05  
LEIPZIGER LEUCHTEN



Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711  
Luminaires generally compensatet

## Light output 1



### 2 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	78%
Lamp flux	1800 lm	Total flux	2815 lm
Luminous efficacy	50 lm/W	Total power	56 W
CCT	2899 K		
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 16.54 in  
Diameter: 16.54 in

## Electric

System power: 56 W

## Protection

IP: 55