

Product data sheet

FLUORESCENT LUMINAIRES
V1-A0-00370-20000-2028LUM 28W OPAL
VARTON




IP
20

IK
02

Versatile fluorescent luminaire. Type of controlling gear: Electronic Ballast. T8 or T5 lamps x4 compatible (not included in package). Application: educational facilities, administrative facilities. Installation: surface-mounted. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YXJ4 Height/depth, mm: 50 Length, mm: 595 Protection class: I Ingress protection (IP): IP20 Impact resistance: IK02 Width, mm: 295 Power factor: 0,95 https://www.varton.ru/products/lyuminestsentnyy-svetilniki/lyum-dlya-obrazovatelnykh-i-administrativnykh-uchrezhdeniy/a370-2kh14-lyum-lamp-vstraivaemye-nakladnye/lyuminestsentnyy-svetilnik-var-ton-a370-2kh14-ofisnyy-vstraivaemy-nakladnoy-595kh295kh50-mm-ip20-s-r_1/

Light output 1



2 x Fluorescent lamp tubular T5

Nominal lamp power	14 W	Socket	G5
Lamp flux	1200 lm	LOR	54%
Luminous efficacy	86 lm/W	Total flux	1284 lm
CCT	4000 K	Total power	28 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 11.61 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 02