


Product data sheet

CIRCULAR OUTWARD Ø600 RECESSED
CF5A-00V9AZRU05
LEDSC4



LedsC4 Circular Outward ø600 Recessed CF5A-00V9AZRU05V1 Pendant for indoor use. For sideways lighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 3.4 Product width or diameter (mm): 604 Product height (mm): 3000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 36.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 11.6. Photobiological risk: RG1. Real flux (lm): 3130. Real lm/W: 80. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 39. Power factor: 0.90. Dimmable equipment included: 0-10V.

Light output 1



1 x LED			
Nominal lamp power	36.5 W	LOR	100%
Lamp flux	3130 lm	ULOR	50%
Luminous efficacy	86 lm/W	Total flux	3130 lm
CCT	2700 K	Total power	36.5 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 36.5 W
Appliance Class: I

Protection

IP: 20