

Product data sheet

VRT3 L244 UHR
VERTECO3
DEXTRA




IP
20



Verteco 3 - IP20 Industrial Luminaire with ultra high rack optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1018 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	141.2 W	CRI	80
Total flux	23544 lm	LOR	100%
Luminous efficacy	167 lm/W	Total power	141.2 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.37 in

Width: 8.46 in

Height: 3.31 in

Adjustability

Fixed

Electric

System power: 141.2 W

Ballast: ECG

Protection

IP: 20

Designation labels: CE