

Product data sheet

DWIDE DELTA VTB 600X600 HL 840
22201
FAGERHULT



IP
20

Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. VTB – for suspended ceilings with visible T-bars 15 or 24 mm. HB – recessed frame allows 600x600 to be installed in suspended ceilings with concealed T-bars and symmetrical ceiling tiles (thickness 20-22 mm). Connection Connection in separate ballast box. Snap-in terminal block 3x1,5 mm² (x2), through-wiring possible. 5x1,5 mm² (x2) when dimming. Can also be supplied with mains cable and earthed plug or chassis mounted snap-in connector. The luminaire housing and driver are connected via a Quick Connection System. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Delta – microprism louvre in acrylic (PMMA) with a thin opal diffuser in acrylic (PMMA) on the inside (PMMA). Light divider in acrylic (PMMA).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	32 W	CRI	80
Total flux	4390 lm	LOR	100%
Luminous efficacy	137 lm/W	Total power	32 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.42 in
Width: 23.43 in
Height: 2.59 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 32 W

Protection

IP: 20