# Product data sheet


URBINO LED S ED 4,5W 450LM 2200K IP66 O5 GRAY I
130772.5L011.050
LUG



IP 66 IK 10

A functionally optimised modern LED luminaire that complements the URBINO LED luminaire family in an environmentally responsible way with solutions for lower power and flux points. Mounting: on pillar, on outriggers, with mounting brackets (to be ordered seperately) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.035 m² Power supply efficiency: ≤93% Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, knife switch, 10kV surge protection, NTC, NEMA connector, ZHAGA connector, version with increased corrosion resistance in accordance with class C5-M, extension of the warranty to 10 years Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, parking areas, Railway stations, residential, public spaces, playgrounds, promenade, local roads, town roads, residential area roads, pedestrian crossings Additional information: the standard version of the luminaire is corrosion resistant according to class C4 Other remarks: the pole and boom are not part of the luminaire Type of optics: O5

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 2200 K |
| Nominal lamp power | 4.5 W | CRI | 70 |
| Total flux | 450 lm | LOR | 100% |
| Luminous efficacy | 100 lm/W | Total power | 4.5 W |

### Mounting mode

Pole top mounted

### Shape and measurements

Length: 18.57 in
Width: 7.82 in
Height: 3.93 in

### Adjustability

Fixed

### Electric

System power: 4.5 W
Appliance Class: I

### Protection

IP: 66
IK: 10