## Product data sheet

LUCAS III (WALL FITTING) 9.837.3046.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



| 1 x High pressure mercury vapour lamp |         |  |
|---------------------------------------|---------|--|
| Nominal lamp power                    | 50 W    |  |
| Lamp flux                             | 2000 lm |  |
| Luminous efficacy                     | 28 lm/W |  |
| CCT                                   | 3400 K  |  |
| CRI                                   | 54      |  |

| LOR         | 84%     |
|-------------|---------|
| Total flux  | 1675 lm |
| Total power | 59 W    |
|             |         |



| 1 x High pressure mercury vapour lamp |         |  |
|---------------------------------------|---------|--|
| Nominal lamp power                    | 80 W    |  |
| Lamp flux                             | 4000 lm |  |
| Luminous efficacy                     | 38 lm/W |  |
| CCT                                   | 3400 K  |  |
| CRI                                   | 54      |  |

| LOR         | 84%     |
|-------------|---------|
| Total flux  | 3351 lm |
| Total power | 89 W    |
|             |         |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 59-89 W

Protection

IP: 55