


Product data sheet

SCOUT 205.940.25.2/DALI-EU 25°
SCOUT 205.940.25.2/DALI-EU
LTS LICHT & LEUCHTEN



flexible track-mounted spotlight in separated design with cylindrical light-head, light-head rotates through 355° and pivots through 90° via integrated articulated arm, outstanding ease of maintenance, no UV and thermal emissions, light-head made from die-cast aluminium, innovative thermal management with design-integrated passive cooling, high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting, ballast housing made from aluminium, clear and reflection-free EnergyVision safety glass, 3-phase track adapter DALI (Eutrac), ballast (LED converter DALI, dimmable) integrated Lamp: LED Spot | 940 | CRI 90 | 4000 K Lifetime: L90 B50 50.000 h / L80 B50 100.000 h / L80 B20 50.000 h EPREL light sources: 848115 beam angle: 25° beam range: 25° Protection class: I Type of protection: IP20 Standards: CE,RoHS Diameter of light head: 96 mm Dimensions (LxBxH): 178 x 96 x 185 mm Weight: 1.288 kg Colour: silver (article no. 660640), black (article no. 660641), white (article no. 660642) Accessories: ZBK 13 anti-glare flaps ZBW 87 honeycomb louvre Manufacture: LTS Type: SCOUT 205.940.25.2/DALI-EU

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	45.8 W	CRI	90
Total flux	5410 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	45.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.38 in
Diameter: 3.78 in

Electric

System power: 45.8 W
Appliance Class: I

Protection

IP: 20