
Product data sheet

2884 SATURNO Ø370 UGR<LT/>25 - ELLIPTICAL 4000K CRI 80 120W CLD-E GRAPHITE
330764-07
DISANO



Housing: in die-cast aluminium with cooling fins integrated in the cover. Optics: in high-performance PMMA resistent to high temperatures and UV rays. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). : UGR<lt/>25 Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - waterproof connector for quick installation with no need to open the fixture - temperature controller with auto-reset - EN 61547 compliant surge protection. - anti-condensation valve Easy installation: -The fixture can be suspended from two attachment points by means of threaded bar (L = 200 mm) and hook to be purchased separately. On request: -Class II fixtures, protection up to 10KV. -Built-in presence/light sensor with ON-OFF function, dimmable (0-10V, 1-10V or DALI) or for ZHAGA socket. -Centralized lighting point control or via external presence/lighting sensors. -CLD D-D (DALI) wiring with subcode -0041. -Emergency wiring with centralized power supply CLD EC (subcode -0050). -AMBER LED 2200K with subcode -73.

Light output 1 (emergency)



1 x LED

Nominal lamp power	120 W	LOR	100%
Lamp flux	18360 lm	Total flux	18358 lm
Luminous efficacy	153 lm/W	Total power	120 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 14.57 in
Width: 14.57 in
Height: 5.28 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 120 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 66
IK: 08
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -40...104°F