Product data sheet

P.THIRTY SUSP. X-SEG.HOR. WHITE DI/ID U 15MM
P30-HXFH9016C2930L1U
PLANLICHT



IP 20 CE

LED LO 3000K 18W 3016lm CRI90 https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.8 W	CRI	90
Total flux	302 lm	LOR	100%
Luminous efficacy	168 lm/W	Total power	1.8 W

Mounting mode

Pendant

Shape and measurements

Length: 8.46 in

Width: 28.43 in

Height: 2.01 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 20

Designation labels: CE