# Product data sheet

LED LINEAR-U3-35W-120*1200-840-SP-B
529000149500
OPPLE



IP 20

Housing:Metal plate; Mounting ring: Black; Installation:Suspended&surface mounted; Dimensions: 1200×120×40mm; Ceiling cutouts: /mm; Beam angle: 110°; Lamp(s): LED; Power:35W; Efficacy:90Lm/w; Total luminous flux of luminaire: 3150lm; Power Factor:0.9; Mains voltage: 220-240V; Colour temperature: 4000K; Colour rendering: 80; UGR: /; IP/IK Grade:IP20; Class of protection Class I; Control System: /; Service life:20000hrsh at 70% luminous flux;

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 35 W | LOR | 100% |
| Lamp flux | 3150 lm | Total flux | 3150 lm |
| Luminous efficacy | 90 lm/W | Total power | 35 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 4.72 in
Width: 47.24 in
Height: 1.57 in

### Adjustability

Fixed

### Electric

System power: 35 W
Appliance Class: I

### Protection

IP: 20