Product data sheet

LUMINO 300 IP44 15W 830/840 PCO
4146668
AIRAM



IP 44 IK 10

Lumino is a low-profile, high-quality and long-lasting universal luminaire for residential buildings and public places. The appearance of the luminaire is finished and the light it gives is uniform and high-quality. Thanks to its low structure, the luminaire fits elegantly and discreetly into various spaces and interiors. The lamp is suitable for indoor and outdoor wall and ceiling installations in stairwells and public spaces. Thanks to the IP44 class, you can also install the luminaire in the bathroom and other damp areas. The luminaire has two color temperatures. You can choose from two size options and a sensor versions from both sizes.

Light output 1



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1500 lm	ULOR	7%
Luminous efficacy	100 lm/W	Total flux	1503 lm
CCT	3000 K	Total power	15 W
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1500 lm	ULOR	7%
Luminous efficacy	100 lm/W	Total flux	1503 lm
CCT	4000 K	Total power	15 W
CRI	80		



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1100 lm	ULOR	7%
Luminous efficacy	92 lm/W	Total flux	1102 lm
CCT	4000 K	Total power	12 W
CRI	80		



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1100 lm	ULOR	7%
Luminous efficacy	92 lm/W	Total flux	1102 lm
CCT	3000 K	Total power	12 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.81 in
Width: 11.81 in
Height: 2.09 in

Adjustability

Fixed

Electric

System power: 12-15 W

Protection

IP: 44
IK: 10