Product data sheet


VELIOS LED LINEAR 300X1200 WHITE 4420LM 4000K RA>80 DALI
5703821162326
SG ARMATUREN



IP 20

Velios Linear was designed for ceilings with visible T-rails. Profiled contrast-reduction panels and high-performance central optics give uniformly diffuse lighting. Energy efficiency of up to 130 lm/W. Exceptional glare control gives high degree of visual comfort. Light distribution Direct Light technic LED 34W 4000K Ra>80 SDCM 3 L90/B10 >50,000 hrs Control/Dimming DALI Protection Class I IP20 Materials and finish Housing: Sheet steel Colour: White smooth (Ral 9016 gloss 30) Optics: PMMA (Acrylate) Mounting/Connection Recessed, Indoor 300x1200 Exposed T-carrier 15/24mm 5 pol Winsta / Terminal block Max. luminaires per circuit breaker: B10: 13, B16: 24, C10: 21, C16: 38

Light output 1



1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4420 lm	Total flux	4405 lm
Luminous efficacy	130 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 11.61 in
Height: 2.56 in

Adjustability

Fixed

Electric

System power: 34 W
Appliance Class: I

Protection

IP: 20