
Product data sheet

ARETE_LED_36W_NEUTRAL_SPOT_L1140MM
133083
PETRIDIS



Technical Features - Luminaires for fluorescent lamps T16 & T26, LED lamp T26 or with LED CHIP. - Steel body, electrostatically painted in white colour. - End caps made of white plastic with high thermal resistance. For LED CHIP version - Linear LED cover from PMMA for LED CHIP version. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux. - Connection for operation on 230V/50Hz. Upon request: - Available with highest colour rendering index (CRI). - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	36 W	LOR	100%
Lamp flux	5860 lm	Total flux	5860 lm
Luminous efficacy	163 lm/W	Total power	36 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.88 in
Width: 2.56 in
Height: 3.39 in

Adjustability

Fixed

Design

Material impression: Chrome, Plastic

Electric

System power: 36 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 20
Designation labels: CE