Product data sheet

OUTDOOR LIGHTING

V1-S1-70760-40U34-6611040 LEVANTE PLAZA 110W 4000K NEMA


VARTON



IP 66 IK 03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: parking, squares and parks. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-plaza-dlya-ploshchadi/svetodiodnyy-svetilnik-varton-ulichnyy-levante-m-plaza-110-vt-kronshteyn-60-mm-4000-k-1-10v-nema-ral/

Light output 1



1 x LED

Nominal lamp power	110 W	LOR	100%
Lamp flux	14300 lm	Total flux	14300 lm
Luminous efficacy	130 lm/W	Total power	110 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 34.45 in

Width: 5.87 in

Height: 4.37 in

Adjustability

Fixed

Electric

System power: 110 W

Protection

IP: 66

IK: 03