




Product data sheet

TIRABO-TRALNA/1500-1 LED - OPTILENS® | OPTILENS®
5400-3200 930 3913LM ETM WS (61513033150)
REGIOLUX



Surface-mounted luminaire; Sheet steel housing, Housing colour white, Textured powder coating, rectangular cross section, longitudinal contour. Light distribution direct asymmetrical distribution by means of OptiLens® of PMMA plastic, homogeneous light distribution in the direction of emission; this combines a slimline design with outstanding functionality, ensuring uniform, pleasant surface illumination with a CRI of 90. The visually brilliant, large-format and homogeneously illuminated lenses create a distinctive aesthetic and a low UGR value. The lighting technology reduces multi-shadow effects and achieves a balance between efficiency, effective glare reduction and compact dimensions for exceptional visual comfort. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Includes multi-lumen driver with adjustable light outputs; flicker < 5%;. Electrical connection via 5-pole connection terminal with plug-in contacts. Including through-wiring. Light can only be operated in conjunction with a single light. Surface-mounted luminaire for ceiling installation. Additional information on the driver switching stages is available on the Internet on the product details page or in the product data sheet under the heading Operating Data. Dimensions (LxWxH): 1402mm x 85mm x 66mm Beam angle: 35°(C0)/95° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 90 / 3000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 100000h L80/B10 (Tq 35°C), 50000h L90/B10 (Tq 35°C) Nominal luminous flux/switching steps (rounded): 5400lm/36W, 4700lm/30W, 3900lm/25W, 3200lm/20W (Standard setting 5384lm) Luminaire luminous efficiency: 158lm/W-151lm/W Control gear: Electronic multi-lumen driver, 4-steps (1 pcs.) System output: 36W-20W Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (10°C bis 35°C) Ambient temperatur: ta 10°C to 35°C UGR lat./long.: 17.5 / 24.6 (36W) Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: tirabo-TRALNA/1500-1 LED 5400-3200 930 ETM ws Article number: 61513033150 Product deep link: <https://www.regiolux.de/en/article/61513033150> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	25.2 W	CRI	90
Total flux	3913 lm	LOR	100%
Luminous efficacy	155 lm/W	Total power	25.2 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 55.20 in
Width: 3.35 in
Height: 2.60 in

Electric

System power: 25.2 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White