


Product data sheet

LUCAS II (WALL FITTING BEADED)
9.836.1072.16
LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| | | | |
|-----------------------|----------|-------------|----------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 150 W | LOR | 83% |
| Lamp flux | 15000 lm | ULOR | 2% |
| Luminous efficacy | 73 lm/W | Total flux | 12434 lm |
| CCT | 2900 K | Total power | 170 W |
| CRI | 90 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in
Diameter: 22.44 in

Electric

System power: 170 W

Protection

IP: 55