


Product data sheet


PURE3 HEXAGON SUSP. SILVER DI/ID SAT. HE
P33H15H-9006C2840L30
PLANLICHT



IP
20


LED LO 4000K 102,7W 14895lm DALI CRI90 <https://katalog.planlicht.com/en-gb/search?q=pure%203>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17.12 W	CRI	90
Total flux	2483 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	34%
		Total power	17.12 W

Mounting mode

Pendant

Shape and measurements

Length: 59.45 in

Width: 51.50 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 102.7 W

Protection

IP: 20