



# Product data sheet

IMPACTF2 1X58W T26 HF E3T L000  
96234344  
THORN LIGHTING




A high performance IP65 dust and moisture resistant luminaire with a high impact resistance. For 1 x 58W T26 lamp(s) with electronic - fixed output circuit and integral 3 hour SelfTest emergency lighting function. Class I electrical. Canopy in light grey glass fibre reinforced polyester. Diffuser in polycarbonate with internal prisms. For surface or suspended mounting. Quick-fix installation brackets are supplied for surface mounting, optional accessory kits are available to help with other mounting options. Lamps to be ordered separately. Dimensions: 1594 x 112 x 112 mm Total power: 54.5 W Weight: 4.08 kg

## Light output 1 (emergency)



1 x General service incandescent lamp			
Nominal lamp power	58 W	LOR	75%
Lamp flux	291 lm	ULOR	16%
Luminous efficacy	34 lm/W	Total flux	219 lm
CCT	3000 K	Total power	6.5 W
CRI	80		

## Light output 2



1 x General service incandescent lamp			
Nominal lamp power	58 W	LOR	75%
Lamp flux	5200 lm	ULOR	16%
Luminous efficacy	72 lm/W	Total flux	3911 lm
CCT	3000 K	Total power	54.5 W
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 62.76 in  
Width: 4.41 in  
Height: 4.41 in  
Weight: 4.1 kg

## Electric

System power: 61 W  
Voltage: 230-240 V AC  
Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Design

Material impression: Plastic

## Protection

IP: 65

IK: 08

Designation labels: CE