


Product data sheet

JUNISTAR SQUARE ISOSAFE DIMITOWARM BLACK 2X 980LM 2000-2800K RA>95
901263
SG ARMATUREN



Attractive double downlight for indoor use with 30-degree 360-degree stepless tilt. Mounted directly in insulation. Well integrated LED chip with DimToWarm 2800K–2000K via phase-dimming or DALI driver (optional). Made of die-cast powder-coated aluminium or brushed steel, glass diffuser. 42-degree scattering angle via reflector. Low flush-mounted 2 x Ø83 hole dimensions. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP44. Light distribution Direct Light technic LED (not exchangeable) 16W 2000-2800K Ra>95 SDCM 3 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II SELV IP44 Energy and approvals A++ CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Glass Mounting/Connection Recessed, Indoor Screwless terminal block

Light output 1 (integrated)



Lamp type	LED	CCT	2800 K
Nominal lamp power	16 W	CRI	95
Total flux	980 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	16 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.89 in

Width: 3.74 in

Height: 1.93 in

Adjustability

Tiltable

Design

Color of housing: Black

Electric

System power: 16 W

Appliance Class: II

Protection

IP: 44