


Product data sheet

DAMP PROOF MAX 1500 S 52W 840 VW IP69
4058075849839
LEDVANCE



Tubular damp-proof luminaires with extra high IP and IK protection. Product features: High luminous efficacy: up to 158 lm/W. Lifetime (L80/B50): up to 100,000 h (at 35 °C). Type of protection: IP66, IP69 (80 °C). Impact resistance: IK10. Ammonia resistant. UV-resistant PMMA diffuser. Compatible to Zhaga Book 7 LED light sources. Product benefits: Uniform light distribution. Flexible application through a wide range of beam angles. Versatile applications due to resistance to many chemicals and UV light. Easy to clean, even at high temperatures with a high-pressure cleaner. Energy savings up to 68 % (compared to luminaires that use fluorescent lamps). Low flicker $\leq 5\%$. Areas of application: Food industry. Open car parks and underpasses. Car wash facilities. Outdoor applications. Industrial and storage facilities. Workshops, assembly lines. Passages, underpasses. Parking garages. Equipment / Accessories: Stainless steel clamps and M20 cable gland included. Safety advice: All electrical connections must be made by a qualified person.. Caution, risk of electric shock.. Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor..

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52 W	CRI	80
Total flux	8000 lm	LOR	100%
Luminous efficacy	154 lm/W	ULOR	8%
		Total power	52 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 68.11 in
Width: 4.92 in
Height: 5.43 in
Weight: 5.3 kg

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 52 W
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -40...113°F