
## Product data sheet

EVA I 9.898.3066.00 LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.00 - 5.00 m. - Impact-resistant opal polyethylene attachment - Large aluminium reflector for max. light output, underside in special white paint - Unit carrier made of die cast aluminium, corrosion-resistant, outside painted in color - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


Light output 1



1 x High pressure mercury vapour larr	р
---------------------------------------	---

IP 55

Nominal lamp power	125 W	LOR	82%
Lamp flux	6800 lm	ULOR	28%
Luminous efficacy	41 lm/W	Total flux	5553 lm
CCT	3400 K	Total power	137 W
CRI	54		



1 x High	pressure	mercurv	vapor	ır lamp

· · · · · <del>2</del> h. · · · · · · · · · · · · · · · · ·			
Nominal lamp power	80 W	LOR	82%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	37 lm/W	Total flux	3267 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode				
Pole top mounted				

## Shape and measurements

Height: 17.72 in Diameter: 15.75 in

## Electric

System power: 89-137 W

## Protection

IP: 55