Product data sheet


FIL45 SUR 1400 3250 9WW OP COMF DALI WH.
F41SF140MOPR930DW
LAMP



IP 20 IK 07

Suspended or mounted surface structure model FIL45 SUR 1400 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<16. Model for LED MID-POWER, colour temperature 3000K with CRI90 and with electronic wiring Dali included. With IP43, except for suspended installation, which becomes IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	25 W	LOR	100%
Lamp flux	2173 lm	Total flux	2170 lm
Luminous efficacy	87 lm/W	Total power	25 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 55.12 in
Width: 1.77 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 20
IK: 07