


# Product data sheet

VEKTER 4 BOLLARD  
VK-10012-ME-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.9 W	CRI	80
Total flux	3094 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	27.9 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.9 W	CRI	80
Total flux	3094 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	27.9 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 26.38 in  
Width: 10.24 in  
Height: 47.24 in  
Weight: 11.2 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 55.8 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C