



Product data sheet

163 LED DAMP-PROOF LIGHT FITTING
163 15L60G2 KE SENS (16302 0098)
SCHUCH



"LED damp-proof light fitting, 39 W, 5970 lm, 153 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI $\geq$ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Corridor mode (DIMC), HF-sensor, Diffuser PMMA satined, Closure Stainless steel (1.4310), Housing Glass fibre reinforced polyester, Colour grey. LED damp-proof light fitting with glass fibre reinforced polyester housing, diffuser, foamed gasket and clips, incl. two safety clips. Powder-coated reflector with highly efficient Zhaga LED modules and dimmable ECG with overload and short circuit protection, dimming mode "Corridor Mode" and integrated motion sensor. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 116,00 mm, Height 88,00 mm, Net weight 2,88 kg."

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39 W	CRI	80
Total flux	5970 lm	LOR	100%
Luminous efficacy	153 lm/W	ULOR	7%
		Total power	39 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 61.89 in
Width: 4.57 in
Height: 3.46 in

Adjustability

Fixed

Electric

System power: 39 W
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 65
IK: 06
Designation labels: CE