


Product data sheet


FIT 35 48V SHORT DOUBLE SPOT DIM DALI 4000K NTW
A3451212NTW-S
ARKOSLIGHT



IP
20


Fit 48V is a spotlight for low voltage tracklight applications, available in different models (50, 35, 35 Double, 27, 27 Double, 20 and 20 Double). With its cylindrical geometry and essential forms, it stands out for its minimalistic design and functionality, as it can be oriented in any direction. The black perimeter around its mouth and its honeycomb accessory highlight its anti-glare vocation.

Light output 1



1 x LED			
Nominal lamp power	5.5 W	LOR	87%
Lamp flux	710 lm	Total flux	618 lm
Luminous efficacy	129 lm/W	Total power	5.5 W
CCT	4000 K		
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	5.5 W	LOR	87%
Lamp flux	710 lm	Total flux	618 lm
Luminous efficacy	129 lm/W	Total power	5.5 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 1.38 in

Width: 6.54 in

Height: 4.53 in

Adjustability

Rotatable, Tilttable

Electric

System power: 11 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20