


# Product data sheet

LINA45-S 145S-2C0I-35GEM3/840, B  
145S-2C0I-35GEM3/840  
HALLA




145S-2C0I-35GEM3/840, B Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1964 x 47 x 69 mm  
Type of installation: Surface Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15.4 W	CRI	80
Total flux	2260 lm	LOR	100%
Luminous efficacy	147 lm/W	Total power	15.4 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	260 lm	LOR	100%
Luminous efficacy	173 lm/W	Total power	1.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 1.85 in  
Width: 77.32 in  
Height: 2.72 in

## Adjustability

Fixed

## Electric

System power: 16.9 W  
Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Protection

IP: 20