Product data sheet


1570 CLIMA - LED 4000K CRI 70 11W CLD
422403-00
DISANO



IP 65 IK 08

Housing: in die-cast aluminium, top cover in aluminium. Attachment: suited for poles with a diameter of 60 mm. Diffuser: in anti-glare polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, externally smooth and dustproof. Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: built-in. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - waterproof connector for quick installation with no need to open the fixture. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - CLD PROG built-in functions. Mounting: on 60 mm diameter pole or bracket.

Light output 1



1 x LED

Nominal lamp power	11 W	LOR	100%
Lamp flux	1806 lm	Total flux	1806 lm
Luminous efficacy	164 lm/W	Total power	11 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 20.24 in
Width: 20.24 in
Height: 16.81 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 11 W
Appliance Class: II

Protection

IP: 65
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F