




# Product data sheet

PRO-CEILING 15W, 168X168MM ZWART  
4000126X  
PROLUMIA




Light source: SMD LED's Color rendering index: Ra>80 Operating temperature: -10°C - +40°C Rated life hours: 35.000 - 50.000 LED driver(included): CE, TUV LED-current: 500mA Input: 220-240Vac, 50/60Hz Power Factor: >0.90 Beam angle: 110°

## Light output 1




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	67 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1070 lm	Total flux	1070 lm
Luminous efficacy	71 lm/W	Total power	15 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	920 lm	Total flux	920 lm
Luminous efficacy	61 lm/W	Total power	15 W
CCT	2700 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 15 W  
Appliance Class: I

### Shape and measurements

Length: 6.61 in

Width: 6.61 in

Height: 1.54 in

### Protection

IP: 40

IK: 08

Designation labels: CE