



Product data sheet

RECESSED CEILING LUMINAIRE SOLO SLIM OFFICE L2 39W 5800LM C
1022.5536 - SOLO SO CR664 LED5800-840 DIR WH DALI
REGENT



Recessed ceiling luminaire Solo Slim Office for false ceilings, with LED, system power: 39 W, standby power 0.5 W, luminous flux of luminaire 5800 lm, colour rendering index CRI > 80, 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 5.9 A, direct light emission, housing in metal, white, without ceiling trim, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0290), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, this product contains a light source of energy efficiency class B Ø = 664 mm, DAØ = 670 mm, ET = 100 mm

Light output 1



1 x LED			
Nominal lamp power	46 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	126 lm/W	Total power	39 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in
Diameter: 26.14 in
Weight: 8.343 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 39 W
Appliance Class: I

Protection

IP: 40