


Product data sheet

LUGTRACK 2 LED 1500 DALI 5450LM 4000K OPAL PLEXIGLASS (PLX) WHITE
080101.3L11.11
LUG



Modern LED luminaire for quick assembly, construction of the luminaire enables quick, easy and tool-less connection into long lighting systems (available in 1,5m and 3m-long dimension) by the usage of mounting elements. Mounting: suspended, on wire suspension (on request) Body: coated steel sheet Power: 220-240V 50/60Hz Lifetime (L80B10): 50 000 h Operating temperature range: 0°C ... +45°C Available on request: DALI, LED emergency module Additional information: Mounting bracket 150110.00654 - purchase only for installation of luminaire according to mounting instruction in variant B. The possibility of using one or more power supplies in the luminaire. Other remarks: through wiring 5x2,5mm (as a standard), connector (1 pcs.) with option of hook installation Warranty: 5 years Application: supermarkets, warehouses, production halls, logistics centers

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47 W	CRI	80
Total flux	5450 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	47 W

Mounting mode

Pendant

Shape and measurements

Length: 59.06 in

Width: 5.08 in

Height: 2.24 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 47 W

Controller: DALI

Appliance Class: I

Protection

IP: 20

IK: 05