


Product data sheet

MACARON 3 CATENARY LUMINAIRES
MC-98001-W-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° > 72,000 - Life time L80B10 Ta 50° > 72,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Stainless steel suspension kit in grade 304 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear, toughened glass lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	104 W	CRI	80
Total flux	13932 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	104 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.71 in
Diameter: 20.35 in
Weight: 13.5 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 104 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C