
Product data sheet

RINGO STAR 60MM SUSPENDED - P3
RG3ASE-840H-D2000-U
LIGHTNET




Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	82
Total flux	1525 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	17 W

Mounting mode

Pendant

Shape and measurements

Length: 2.36 in
Width: 30.12 in
Height: 3.94 in

Adjustability

Height adjustable

Electric

System power: 136 W

Protection