



# Product data sheet

164KL LED COMPACT LIGHT FITTING  
164KL L11G2 RR (16407 0063)  
SCHUCH



LED compact light fitting, 10 W, 1150 lm, 115 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI $\geq$  80, Ta -20 °C/+30 °C, L80>50000 h (@ Ta max), Diffuser PMMA satined, Closure Plastic, Housing Glass fibre reinforced polyester, Colour grey. Compact LED damp-proof light fitting with glass fibre reinforced polyester housing, frosted diffuser, silicone gasket and clips. Powder-coated reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 380,00 mm, Width/Diameter 200,00 mm, Height 100,00 mm, Net weight 0,99 kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	1150 lm	LOR	100%
Luminous efficacy	115 lm/W	ULOR	7%
		Total power	10 W

## Mounting mode

Ceiling mounted, Wall mounted

## Shape and measurements

Length: 14.96 in  
Width: 7.87 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 10 W  
Appliance Class: I

## Protection

IP: 65  
IK: 04  
Designation labels: CE