


Product data sheet

LALUNA 3 POST TOP LUMINAIRES
LL-20002-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - White coated aluminium reflector on the top of luminaire

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	47.6 W	CRI	80
Total flux	2270 lm	LOR	100%
Luminous efficacy	48 lm/W	ULOR	2%
		Total power	47.6 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 20.28 in
Diameter: 39.37 in
Weight: 17.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 47.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C