Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, LENS WALLWASHER

AF2105108-33-30 36W


SCHMITZ | WILA





alphabet focus LED 3000 K Recessed Luminaire, Light distribution direct, asymmetric Wallwasher Lens Wallwasher Product: AF2105108-33-30 Operating technology: independent driver required Lens wall washer create a uniform illumination on vertical surfaces without any hard shadow. Room proportions can be perfectly emphasized thanks to a harmonious brightness distribution. Light Technique asymmetric light distribution highly precise optical system, combining primary focus lens and secondary light control lens CRI > 90 constant colour temperature 3000K chromaticity stability with <3SDCM lifetime 50.000 h (L70) aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2mm for homogeneous appearance in the ceiling frame colour white, RAL9016 Operating and assembly technology Order LED gear box separately Gear boxes suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 36 W Colour Rendering Index: 90 Colour Temperature: 3000 K Luminaire Luminous Flux: 1910 Llm System Efficiency: 49 Llm/W Number Luminaires LZ: 0.07 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: Q15 Length: 177 mm Width: 177 mm Cut-out length: 170 mm Cut-out width: 170 mm Overhang OH: 145 mm Installation Depth RD: 200 mm Total Weight: 1.7 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2105108-33-30 36W

Light output 1



1 x General service incandescent lamp

Nominal lamp power Lamp flux Luminous efficacy CCT CRI

39 W 1910 lm 49 lm/W 3000 K

90

Total flux Total power

I OR

100% 1910 lm 39 W

Mounting mode	Electric
Ceiling recessed	System power: 39 W
Shape and measurements	Appliance Class: II
Length: 6.97 in	Protection
Width: 6.97 in	IP: 20
Height: 7.87 in	

Adjustability

Fixed

Design

Color of housing: White