

Product data sheet


A40-W600 LED 1000 840
GLAMOX



IP
44

Light source 1 x T5 14, 24, 28, 35W Supplied with or without light sources LED A40-W LED 1000 - 2800 lumen out Light source information: 3000/4000 Kelvin, CRI 80, MacAdams 3. Lifetime LED: Up to 60.000h Ta25. Driver Electronic ballast (HF) or DALI Body material & colour Body is in steel and the diffuser in triple extruded acrylic, with white or metalized end caps in a synthetic material. Available in three different lengths and with or without concealed outlet at the end of the luminaire Mounting Vertical or horizontally directly to walls or to bathroom fixtures Connection 3/5 pole push-in terminal block ready for through wiring. 2 grommets (Ø19 mm) placed on the reverse side. Surface mounted cable can enter the luminaires from all directions. Outlet has possibilities to be connected to direct power Integrated sensors Ultra sonic movement sensor type UB-SEN for LED variants The U-SEN master can switch on/off slave luminaries, but have a limitation on 4 electronic (HF) ballast due to the inrush current.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	990 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	84%
		Total power	9 W

Mounting mode

Wall mounted

Shape and measurements

Length: 23.62 in
Width: 2.24 in
Height: 2.87 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 44