Product data sheet

FLEXBAR SURFACE / SUSPENDED - 8W (6W/M) - PRIMARY CORNER - LEFT - UP & DOWNLIGHT - WHITE REF - 4000K FR08CPLUW


THORLUX LIGHTING



IP 20


Flexbar is an elegant surface mounted or suspended linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	725 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	18%
		Total power	5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	725 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	18%
		Total power	5 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 34.25 in
Width: 1.73 in
Height: 2.40 in

Adjustability

Fixed, Height adjustable

Electric

System power: 10 W

Protection

IP: 20